



## 3~ NUMINOS® PHASE M

3 phase system light white/black 2700K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the 3~ NUMINOS® PHASE M 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1925 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS® from SLV?

## TECHNICAL DATA

|                                 |                         |
|---------------------------------|-------------------------|
| Item no.                        | 1004174                 |
| Rotating or tilting             | rotary Bar and tiltable |
| Assembly details                | Track Ceiling           |
| Dimmable                        | Yes                     |
| Dimming technology              | trailing edge           |
| Primary nominal voltage         | 220-240V ~50/60Hz       |
| Secondary power / voltage       | 500 mA                  |
| Safety class                    | I                       |
| Wattage                         | 20.1 W                  |
| Minimum ambient temperature     | -20 °C                  |
| Maximum ambient temperature     | 30 °C                   |
| Number of luminaires at LS B16A | 50                      |
| Number of luminaires at LS C16A | 85                      |
| Level of inrush current         | 13 A                    |
| Duration of inrush current      | 30 µs                   |
| Lumen                           | 1925 lm                 |
| Colour temperature              | 2700 Kelvin             |
| Beam angle                      | 24 °                    |
| Color                           | white                   |
| CRI                             | 90                      |
| UGR ≤                           | 16                      |
| LXXBXX data                     | L80B50                  |

Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

Accessories

|         |                               |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Length             | 18.5 cm              |
| Height             | 16.5 cm              |
| Diameter           | 8.5 cm               |
| Net weight         | 0.77 kg              |
| Gross weight       | 1.06 kg              |
| BIG WHITE Page     | 112                  |