




## NUMINOS® SPOT PHASE M

Indoor LED surface-mounted ceiling light white/black 3000K 36°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® SPOT PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1970 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.	1004207
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	85
Level of inrush current	13 A
Duration of inrush current	30 µs
Lumen	1970 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	13

Light Source

791822	
--------	---

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	18.5 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.83 kg
Gross weight	1.125 kg
BIG WHITE Page	100