


## NUMINOS® PD PHASE M

Indoor LED pendant light white/black 3000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® PD PHASE M pendant light, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 1955 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                 |                            |
|---------------------------------|----------------------------|
| Item no.                        | 1004254                    |
| Assembly                        | Surface                    |
| Assembly details                | Ceiling, Ceiling with Acc. |
| Dimmable                        | Yes                        |
| Dimming technology              | trailing edge              |
| Primary nominal voltage         | 220-240V ~50/60Hz          |
| Secondary power / voltage       | 500 mA                     |
| Safety class                    | I                          |
| Wattage                         | 20.1 W                     |
| Minimum ambient temperature     | -20 °C                     |
| Maximum ambient temperature     | 30 °C                      |
| Number of luminaires at LS B16A | 50                         |
| Number of luminaires at LS C16A | 85                         |
| Level of inrush current         | 13 A                       |
| Duration of inrush current      | 30 µs                      |
| Lumen                           | 1955 lm                    |
| Colour temperature              | 3000 Kelvin                |
| Beam angle                      | 24 °                       |
| Color                           | white                      |
| CRI                             | 90                         |
| UGR ≤                           | 16                         |
| LXXBXX data                     | L80B50                     |

Light Source

|        |   |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

|         |                               |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|

|                    |                      |
|--------------------|----------------------|
| Service life       | 50000 h              |
| Light distribution | rotational symmetric |
| Light outlet       | direct               |
| Risk Group         | 1                    |
| Height             | 18.5 cm              |
| Diameter           | 8.5 cm               |
| Pendant length     | 250 cm               |
| Net weight         | 1 kg                 |
| Gross weight       | 1.2 kg               |
| BIG WHITE Page     | 108                  |