



3~ NUMINOS® PHASE L

3 phase system light white/black 4000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NUMINOS® PHASE L 3-phase system light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2715 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| | |
|---------------------------------|-------------------------|
| Item no. | 1004288 |
| Rotating or tilting | rotary Bar and tiltable |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 34 |
| Number of luminaires at LS C16A | 58 |
| Level of inrush current | 6 A |
| Duration of inrush current | 40 µs |
| Lumen | 2715 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Length | 21.3 cm |
| Height | 18 cm |
| Diameter | 10 cm |
| Net weight | 1.098 kg |
| Gross weight | 1.43 kg |
| BIG WHITE Page | 113 |