




## NUMINOS® SPOT PHASE L

Indoor LED recessed ceiling light white/black 3000K 24°

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® SPOT PHASE L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2430 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



### TECHNICAL DATA

Item no.	1004302
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	34
Number of luminaires at LS C16A	58
Level of inrush current	6 A
Duration of inrush current	40 µs
Lumen	2430 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	13

Light Source

791822	
--------	---

Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.08 kg
Gross weight	1.425 kg
BIG WHITE Page	101