




NUMINOS® PD PHASE L

Indoor LED pendant light white/black 3000K 24°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light can convince with a power consumption of 28 watts, luminous flux of 2430 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|---------------------------------|----------------------------|
| Item no. | 1004350 |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 34 |
| Number of luminaires at LS C16A | 58 |
| Level of inrush current | 6 A |
| Duration of inrush current | 40 µs |
| Lumen | 2430 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Pendant length | 250 cm |
| Net weight | 1.3 kg |
| Gross weight | 1.5 kg |
| BIG WHITE Page | 109 |