




NUMINOS® SPOT DALI S

Indoor LED recessed ceiling light white/black 3000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® SPOT DALI S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1004398
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	13

Light Source

791815	
--------	---

Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.66 kg
Gross weight	0.95 kg
BIG WHITE Page	100