




## NUMINOS® SPOT DALI S

Indoor LED recessed ceiling light white/black 4000K 36°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® SPOT DALI S indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1100 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.	1004407
Rotating or tilting	rotary Bar and tiltable
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10.42 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	72
Number of luminaires at LS C16A	122
Level of inrush current	52 A
Duration of inrush current	1 µs
Lumen	1100 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	16

## Light Source

791831	
--------	---

## Accessories

1006167	NUMINOS® S , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	16.2 cm
Height	14.5 cm
Diameter	6.5 cm
Net weight	0.66 kg
Gross weight	0.95 kg
BIG WHITE Page	100