




NUMINOS® SPOT DALI M

Indoor LED recessed ceiling light white/black 2700K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® SPOT DALI M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1885 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|---------------------------------|-------------------------|
| Item no. | 1004488 |
| Rotating or tilting | rotary Bar and tiltable |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 20.1 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 8 |
| Number of luminaires at LS C16A | 16 |
| Level of inrush current | 10 A |
| Duration of inrush current | 30 µs |
| Lumen | 1885 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |

Light Source

| | |
|--------|---|
| 791800 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|

| | |
|----------------|---------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 18.5 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.89 kg |
| Gross weight | 1.19 kg |
| BIG WHITE Page | 100 |