



NUMINOS® CL DALI M

Indoor LED surface ceiling light black/black 2700K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® CL DALI M indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1925 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1004506
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	16
Level of inrush current	10 A
Duration of inrush current	30 µs
Lumen	1925 lm
Colour temperature	2700 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50

Light Source

791800	
--------	-----------------------------------------------------------------------------------

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.75 kg
Gross weight	1 kg
BIG WHITE Page	104