



NUMINOS® CL DALI L

Indoor LED surface ceiling light white/black 3000K 60°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® CL DALI L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2400 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1004616 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Number of luminaires at LS B16A | 35 |
| Number of luminaires at LS C16A | 60 |
| Level of inrush current | 30 A |
| Duration of inrush current | 2 µs |
| Lumen | 2400 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|-----------------------------------------------------------------------------------|
| 791822 |  |
|--------|-----------------------------------------------------------------------------------|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

| | |
|--------------------|----------------------|
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Risk Group | 1 |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Net weight | 1.025 kg |
| Gross weight | 1.33 kg |
| BIG WHITE Page | 105 |