




## NUMINOS® PD DALI L

Indoor LED pendant light black/black 4000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® PD DALI L, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 28 watts, luminous flux of 2715 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.	1004644
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	35
Number of luminaires at LS C16A	60
Level of inrush current	30 A
Duration of inrush current	2 µs
Lumen	2715 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50

## Light Source

791825	
--------	---

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Pendant length	250 cm
Net weight	1.55 kg
Gross weight	1.7 kg
BIG WHITE Page	109