


## NUMINOS® PD DALI L

Indoor LED pendant light white/black 4000K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® PD DALI L pendant light, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2620 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.	1004647
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	35
Number of luminaires at LS C16A	60
Level of inrush current	30 A
Duration of inrush current	2 µs
Lumen	2620 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50

## Light Source

791825	
--------	-----------------------------------------------------------------------------------

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	21.3 cm
Diameter	10 cm
Pendant length	250 cm
Net weight	1.55 kg
Gross weight	1.7 kg
BIG WHITE Page	109