




RUSTY® UP/DOWN WL

outdoor LED surface-mounted wall light round rust
CCT switch 3000/4000K


In multi-faceted rust tones, RUSTY® UP/DOWN gives an attractive appearance to facades. For a unique look that will give this wall-mounted light a contrasting effect on any surface. This is made possible by the special chemical treatment of the FeCSI steel used, which only becomes more beautiful as it is exposed to the elements. These indirect lights are fitted with energy-efficient and long-lasting SMD LEDs. To alter the lighting mood, select the desired light colour before installation using the integrated CCT switch (3000K/4000K). RUSTY® UP/DOWN is easy to install and perfectly suitable for outdoor areas thanks to its IP65 protection rating.



TECHNICAL DATA

Item no.	1004651
Number of different light outlets	2
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	9 A
Duration of inrush current	140 µs
Stroboscopic effect (SVM)	0.04
Lumen	516/525 lm
Colour temperature	3000/4000 Kelvin
Beam angle	65 °
Color	rust
CRI	80
LXXBXX data	L70B50

Light Source

916603	
--------	---

Service life	25000 h
Light outlet	direct - indirect
Risk Group	1
Width	14 cm
Height	18 cm
Depth	16.5 cm
Net weight	3.63 kg
Gross weight	4.129 kg
BIG WHITE Page	756