




## OCULUS DL MOVE

Indoor LED ceiling recessed light black  
DIM-TO-WARM 2000-3000K


With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



## TECHNICAL DATA

Item no.	1004669
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Dim-to-Warm, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	80
Number of luminaires at LS C16A	80
Level of inrush current	2 A
Duration of inrush current	50 µs
Stroboscopic effect (SVM)	0.09
Lumen	36-780 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °

Light Source

916608		Color	white
		CRI	90
		LXXBXX data	L80B20
		Service life	40000 h
		Risk Group	1
		Height	7.3 cm
		Diameter	12 cm
		Net weight	0.568 kg
		Gross weight	0.771 kg
		Shape of cut-out	round
		Installation depth	8 cm
		Installation diameter	10.8 cm
		BIG WHITE Page	229