




OCULUS PD

Indoor LED pendant light single white DIM-TO-WARM
2000-3000K

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light (2000-3000K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



TECHNICAL DATA

Item no.	1004673
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Pendant Profile
Dimmable	Yes
Dimming technology	Dim-to-Warm,trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	II
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	13 A
Duration of inrush current	8 µs
Stroboscopic effect (SVM)	0.09
Lumen	35,6-780 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	white
CRI	90
LXXBXX data	L70B50

Light Source

916608	
--------	---

Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	9 cm
Diameter	9 cm
Pendant length	250 cm
Net weight	0.662 kg
Gross weight	0.79 kg
BIG WHITE Page	294