




ONE 60 PD DALI UP/DOWN

Indoor LED pendant light black CCT switch 3000/4000K


Reduced and modern at the same time, the lights of the ONE family attract all eyes. Added to this is the high CRI of over 90 for true-to-life colour reproduction. The low-maintenance light is equally suitable for the hotel industry and gastronomy as well as for living spaces. Experience ONE in action and convince yourself of a successful lighting experience.



TECHNICAL DATA

Item no.	1004761
Number of different light outlets	2
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	600 mA
Safety class	I
Wattage	25 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Rated standby power	0.5 W
Level of inrush current	30 A
Duration of inrush current	2 µs
Stroboscopic effect (SVM)	0.07
Lumen	800/820 lm
Colour temperature	3000/4000 Kelvin
Beam angle	130 °
Color	black
CRI	90

Light Source

916319		LXXBXX data	L70B50
		Service life	30000 h
		Risk Group	1
		Height	4.5 cm
		Diameter	60 cm
		Pendant length	300 cm
		Net weight	2.228 kg
		Gross weight	4.174 kg
		BIG WHITE Page	188