




ONE 60 PD DALI UP/DOWN

Indoor LED pendant light white CCT switch
3000/4000K


Reduced, modern and elegant, the design of the ONE light family attracts all eyes. With a CRI above 90, it provides natural colour reproduction. The low-maintenance light is equally suitable for the hotel industry and gastronomy as well as for living spaces. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1004762 |
| Number of different light outlets | 2 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 600 mA |
| Safety class | I |
| Wattage | 25 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Rated standby power | 0.5 W |
| Level of inrush current | 30 A |
| Duration of inrush current | 2 µs |
| Stroboscopic effect (SVM) | 0.07 |
| Lumen | 800/820 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 130 ° |
| Color | white |
| CRI | 90 |

Light Source

| | | | |
|--------|---|----------------|----------|
| 916319 |  | LXXBXX data | L70B50 |
| | | Service life | 30000 h |
| | | Risk Group | 1 |
| | | Height | 4.5 cm |
| | | Diameter | 60 cm |
| | | Pendant length | 300 cm |
| | | Net weight | 2.256 kg |
| | | Gross weight | 3.895 kg |
| | | BIG WHITE Page | 188 |