




ONE 80 PD DALI UP/DOWN

Indoor LED pendant light black CCT switch 3000/4000K

The modern design of the ONE light family attracts all eyes. Added to this is the high CRI of over 90 for optimal colour reproduction. The low-maintenance light is equally suitable for the hotel industry and gastronomy as well as for living spaces. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

Item no.	1004763
Number of different light outlets	2
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	800 mA
Safety class	I
Wattage	34 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Rated standby power	0.5 W
Level of inrush current	35 A
Duration of inrush current	2 µs
Stroboscopic effect (SVM)	0.08
Lumen	1230/1270 lm
Colour temperature	3000/4000 Kelvin
Beam angle	130 °
Color	black
CRI	90

Light Source

916568	
--------	---

LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Height	4.5 cm
Diameter	80 cm
Pendant length	300 cm
Net weight	2.576 kg
Gross weight	5.431 kg
BIG WHITE Page	188