


PANEL TRACK square 150x300mm

1-phase spot, white, 18W 3000K


Modern and space-saving at the same time, PANEL provides efficient basic lighting. With 1,800 lumens and 3,000 Kelvin, the 1-phase system light LED produces a pleasant, homogeneous and glare-free light. Added to this are the robust construction of the light made of polycarbonate (P-C) and steel and the long LED lifespan of 50,000 hours. Experience PANEL in action and convince yourself of a successful lighting experience.



TECHNICAL DATA

Item no.	1004934
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Impact resistance	0.2 Joule
Assembly details	Track Ceiling, Track Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	450 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.01
Lumen	1800 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
UGR ≤	27.5
LXXBXX data	L70B50
Service life	50000 h

Light Source

916390		Light distribution	rotational symmetric
		Light outlet	direct
		Risk Group	1
		Length	30 cm
		Width	15 cm
		Height	10.9 cm
		Net weight	0.552 kg
		Gross weight	0.71 kg
		BIG WHITE Page	507