




PANEL TRACK round 200mm

1-phase spot, black, 18W 3000K


With the modern and space-saving PANEL, you provide efficient basic lighting. A pleasant, homogeneous and glare-free light is produced by the 1-phase system light LED with 1,800 lumen and 3,000 Kelvin. The light is made of polycarbonate (PC) and steel and has a long LED lifespan of 50,000 hours. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.



TECHNICAL DATA

| | |
|-----------------------------------|---------------------------|
| Item no. | 1004935 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track Ceiling, Track Wall |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 450 mA |
| Safety class | II |
| Wattage | 18 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 15 A |
| Duration of inrush current | 20 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 1800 lm |
| Colour temperature | 3000 Kelvin |
| Color | black |
| CRI | 90 |
| LXXBXX data | L70B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |

Light Source

| | | | |
|--------|---|----------------|----------|
| 916407 |  | Light outlet | direct |
| | | Risk Group | 1 |
| | | Length | 23.1 cm |
| | | Width | 20 cm |
| | | Height | 11.05 cm |
| | | Net weight | 0.446 kg |
| | | Gross weight | 0.602 kg |
| | | BIG WHITE Page | 507 |