Specialist • Lighting • Vendor





NUMINOS® MOVE S

white recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1005353
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	250 mA
Safety class	III
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	730 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
	1

Specialist • Lighting • Vendor



Light Source

791815	A E	
Accessories		
1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI	
1004789	NUMINOS® S , diffuser Wabe	
1004067	LED driver , 15W 250mA DALI	
1004788	NUMINOS® S , diffuser Frosted	
1004787	NUMINOS® S , diffuser Prisma	
1004786	NUMINOS® S , diffuser Ellipse	
1006139	Numinos® S Reducing ring , round 160/100mm black	
1006454	RF module Casambi for LED bridge driver , single colour	
1004058	LED driver , 6.5-10W 250mA	
1006199	RF module Zigbee for DALI LED bridge driver , single colour	
1006140	Numinos® S Reducing ring , round 160/100mm white	
1006142	Numinos® S Reducing ring , square 160/100mm white	
1004055	LED driver , 6.5-10W 250mA PHASE	
1006141	Numinos® S Reducing ring , square 160/100mm black	

Height 6.35 cm Diameter 10 cm Net weight 0.22 kg Gross weight 0.26 kg Shape of cut-out round Installation depth 8.5 cm Installation diameter 9 cm BIG WHITE Page 86		
Net weight 0.22 kg Gross weight 0.26 kg Shape of cut-out round Installation depth 8.5 cm Installation diameter 9 cm	Height	6.35 cm
Gross weight 0.26 kg Shape of cut-out round Installation depth 8.5 cm Installation diameter 9 cm	Diameter	10 cm
Shape of cut-out round Installation depth 8.5 cm Installation diameter 9 cm	Net weight	0.22 kg
Installation depth 8.5 cm Installation diameter 9 cm	Gross weight	0.26 kg
Installation diameter 9 cm	Shape of cut-out	round
	Installation depth	8.5 cm
BIG WHITE Page 86	Installation diameter	9 cm
	BIG WHITE Page	86