Specialist • Lighting • Vendor






SIGHT TRACK DALI

black 3-phase spot, CCT

The modern SIGHT wall and ceiling light is made for surface mounting or busbar. In black, the light made of aluminium and acrylic cuts a professional figure everywhere. With its lifespan of 30,000 hours, the LED is also extremely sustainable. When will you test out the benefits of SLV's impressive indoor lights?




TECHNICAL DATA

| Item no. | 1005397 |
|-----------------------------|-------------------|
| IP Code | IP 20 |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 39 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Rated standby power | 0.5 W |
| Network rated standby power | 0.5 W |
| Level of inrush current | 26 A |
| Duration of inrush current | 140 μs |
| Stroboscopic effect (SVM) | 0.03 |
| Lumen | 3000/3000 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 120 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 25 |
| | |

Specialist • Lighting • Vendor



Light Source



| LXXBXX data | L70B50 |
|----------------|----------|
| Service life | 30000 h |
| Risk Group | 1 |
| Length | 114 cm |
| Width | 4.5 cm |
| Height | 12 cm |
| Net weight | 2.106 kg |
| Gross weight | 2.6 kg |
| BIG WHITE Page | 532 |