



## MILANDOS 4



white recessed ceiling light, 3000K 45°

The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a high colour reproduction index of over 90 out of 60,000. With a UGR of 23, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.

### TECHNICAL DATA

Item no.	1005410
IP Code	IP 20
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	8 W
Ambient temperature	30 °C
Lumen	650 lm
Colour temperature	3000 Kelvin
Beam angle	45 °
Color	white
CRI	90
UGR ≤	23
LXXBXX data	L80B50
Service life	60000 h
Risk Group	1
Length	13.6 cm
Width	5.6 cm
Height	4.3 cm
Net weight	0.25 kg

### Light Source

1078215	
998089	

### Accessories

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1002423	LED driver MEDO 300 , dimmable DALI/1-10V

Gross weight	0.268 kg
Shape of cut-out	square
Installation length	13 cm
Installation width	4.9 cm
Installation depth	7 cm
BIG WHITE Page	217