

MILANDOS 8



black recessed ceiling light, 3000K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The true-to-life colour reproduction index of over 90 and the long LED lifespan of 60,000 hours also speak for the light. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?

TECHNICAL DATA

Item no.	1005424
IP Code	IP 20
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	16 W
Ambient temperature	30 °C
Lumen	1040 lm
Colour temperature	3000 Kelvin
Beam angle	45 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50
Service life	60000 h
Risk Group	1
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Net weight	0.388 kg

Light Source

1078215	
998089	

Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Gross weight	0.476 kg
Shape of cut-out	square
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
BIG WHITE Page	217