Specialist • Lighting • Vendor





NUMINOS® MOVE XS

white / black recessed ceiling light, 2700K 55°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| Item no. | 1005568 |
|-----------------------------|-------------------------|
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 640 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 25 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 5.5 cm |
| | |

Specialist • Lighting • Vendor



Light Source

| 798300 | â F | |
|-------------|--|--|
| Accessories | | |
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white | |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black | |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector | |
| 1005614 | NUMINOS® XS , frosted diffuser | |
| 1006454 | RF module Casambi for LED bridge driver , single colour | |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour | |
| 1005612 | NUMINOS® XS , diffuser | |
| 1005610 | LED Driver , 200mA 10- W, Quick Connector | |
| 1005615 | NUMINOS® XS , black diffuser | |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black | |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector | |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white | |
| 1005613 | NUMINOS® XS , transparent diffuser | |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI | |

| Diameter | 8 cm |
|-----------------------|----------|
| Net weight | 0.135 kg |
| Gross weight | 0.165 kg |
| Shape of cut-out | round |
| Installation depth | 8 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 86 |