## Specialist • Lighting • Vendor





## **NUMINOS® XL PHASE**

black ceiling mounted light, 36W 4000K  $60^{\circ}$ 

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XL PHASE indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3460 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

#### **TECHNICAL DATA**

| Item no.                          | 1005701           |
|-----------------------------------|-------------------|
| Number of different light outlets | 1                 |
| Assembly                          | Surface           |
| Assembly details                  | Ceiling           |
| Dimmable                          | Yes               |
| Dimming technology                | trailing edge     |
| Primary nominal voltage           | 220-240V ~50/60Hz |
| Secondary power / voltage         | 900 mA            |
| Safety class                      | 1                 |
| Wattage                           | 36 W              |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 35 °C             |
| Level of inrush current           | 4.64 A            |
| Duration of inrush current        | 224 µs            |
| Stroboscopic effect (SVM)         | 0.02              |
| Lumen                             | 3460 lm           |
| Colour temperature                | 4000 Kelvin       |
| Beam angle                        | 60 °              |
| Color                             | black             |
| CRI                               | 90                |
| UGR≤                              | 25                |
| LXXBXX data                       | L80B50            |
|                                   |                   |

# Specialist • Lighting • Vendor



### Light Source

| 791850      | A E                            |
|-------------|--------------------------------|
| Accessories |                                |
| 1006170     | NUMINOS® XL , white front ring |

| Service life   | 50000 h |
|----------------|---------|
| Risk Group     | 1       |
| Height         | 25.8 cm |
| Diameter       | 12 cm   |
| Net weight     | 1.63 kg |
| Gross weight   | 2 kg    |
| BIG WHITE Page | 105     |