




NUMINOS® XL PHASE

black pendant light, 36W 3000K 60°


The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® XL PHASE pendant light, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3210 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1005713
Number of different light outlets	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	3210 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	25
LXXBXX data	L80B50

Light Source

791823		Service life	50000 h
		Risk Group	1
		Height	25.8 cm
		Diameter	12 cm
		Pendant length	250 cm
		Net weight	2 kg
		Gross weight	2.25 kg
		BIG WHITE Page	105