




NUMINOS® XL PHASE

white / black pendant light, 36W 3000K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XL PHASE, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3210 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1005716 |
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Level of inrush current | 4.64 A |
| Duration of inrush current | 224 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3210 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791823 |  |
|--------|---|

| | |
|----------------|---------|
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Pendant length | 250 cm |
| Net weight | 2 kg |
| Gross weight | 2.25 kg |
| BIG WHITE Page | 105 |