



NUMINOS® XL PHASE

white / black 3-phase spot, 36W 3000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XL PHASE 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3210 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1005734
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	3210 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B50

Light Source

791823	
--------	---

Service life	50000 h
Risk Group	1
Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.63 kg
Gross weight	2 kg
BIG WHITE Page	113