



## NUMINOS® DALI XL

black 3-phase spot, 36W 2700K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DALI XL 3-phase system light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3290 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005795                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly details                  | Track Ceiling           |
| Dimmable                          | Yes                     |
| Dimming technology                | DALI                    |
| Primary nominal voltage           | 220-240V ~50/60Hz       |
| Secondary power / voltage         | 900 mA                  |
| Safety class                      | I                       |
| Wattage                           | 36 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 35 °C                   |
| Number of luminaires at LS B16A   | 18                      |
| Number of luminaires at LS C16A   | 18                      |
| Level of inrush current           | 15 A                    |
| Duration of inrush current        | 100 µs                  |
| Stroboscopic effect (SVM)         | 0                       |
| Lumen                             | 3290 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 24 °                    |
| Color                             | black                   |
| CRI                               | 90                      |

Light Source

|        |   |
|--------|---|
| 791857 |  |
|--------|---|

Accessories

|         |                                |
|---------|--------------------------------|
| 1006170 | NUMINOS® XL , white front ring |
|---------|--------------------------------|

|                |         |
|----------------|---------|
| UGR ≤          | 19      |
| LXXBXX data    | L80B50  |
| Service life   | 50000 h |
| Risk Group     | 1       |
| Length         | 25.8 cm |
| Height         | 20 cm   |
| Diameter       | 12 cm   |
| Net weight     | 1.55 kg |
| Gross weight   | 1.95 kg |
| BIG WHITE Page | 113     |