



## NUMINOS® GIMBLE XS

black / chrome recessed ceiling light, 4000K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005851                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 200 mA                  |
| Safety class                      | III                     |
| Wattage                           | 7 W                     |
| Lumen                             | 750 lm                  |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 20 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 16                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Height                            | 5.7 cm                  |
| Diameter                          | 8 cm                    |
| Net weight                        | 0.13 kg                 |
| Gross weight                      | 0.15 kg                 |
| Shape of cut-out                  | round                   |
| Installation depth                | 8 cm                    |

## Light Source

|        |   |
|--------|---|
| 798305 |  |
|--------|---|

|                       |        |
|-----------------------|--------|
| Installation diameter | 6.8 cm |
|-----------------------|--------|

## Accessories

|                |    |
|----------------|----|
| BIG WHITE Page | 88 |
|----------------|----|

|         |  |
|---------|--|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white   |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black   |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector  |
| 1005614 | NUMINOS® XS , frosted diffuser   |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1005612 | NUMINOS® XS , diffuser   |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector   |
| 1005615 | NUMINOS® XS , black diffuser   |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black  |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector                                    |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white  |
| 1005613 | NUMINOS® XS , transparent diffuser   |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |