



## NUMINOS® GIMBLE XS

black / chrome recessed ceiling light, 4000K 40°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

### TECHNICAL DATA

Item no.	1005854
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Lumen	730 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Height	5.7 cm
Diameter	8 cm
Net weight	0.13 kg
Gross weight	0.15 kg
Shape of cut-out	round
Installation depth	8 cm

Light Source

798305	
--------	---

Installation diameter	6.8 cm
-----------------------	--------

Accessories

BIG WHITE Page	88
----------------	----

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006135	Numinos® XS Reducing ring , round 160/70mm black
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70mm black
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1006138	Numinos® XS Reducing ring , square 160/70mm white
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI