



## NUMINOS® GIMBLE M

white / black recessed ceiling light, 4000K 55°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005972                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 500 mA                  |
| Safety class                      | III                     |
| Wattage                           | 17.5 W                  |
| Lumen                             | 1600 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 9.5 cm                  |
| Diameter                          | 13.5 cm                 |
| Net weight                        | 0.45 kg                 |
| Gross weight                      | 0.55 kg                 |
| Shape of cut-out                  | round                   |

## Light Source

|        |   |
|--------|---|
| 791825 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1004792 | NUMINOS® M , diffuser Frosted  |
| 1004069 | LED driver , 29W 500mA   |
| 1004064 | LED driver , 21-29.5W 500/600/700mA  |
| 1006459 | LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006143 | Numinos® M Reducing ring , round 240/120mm black   |
| 1004054 | LED driver , 20W 500mA PHASE   |
| 1006146 | Numinos® M Reducing ring , square 240/120mm white  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006144 | Numinos® M Reducing ring , round 240/120mm white   |
| 1004793 | NUMINOS® M , diffuser Wabe   |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006145 | Numinos® M Reducing ring , square 240/120mm black  |
| 1004790 | NUMINOS® M , diffuser Ellipse  |
| 1004791 | NUMINOS® M , diffuser Prisma   |

|                       |        |
|-----------------------|--------|
| Installation depth    | 9.5 cm |
| Installation diameter | 12 cm  |
| BIG WHITE Page        | 89     |