



NUMINOS® GIMBLE L

black / chrome recessed ceiling light, 4000K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® GIMBLE L recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1006013 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 25.4 W |
| Lumen | 2350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 11.5 cm |
| Diameter | 16 cm |
| Net weight | 0.6 kg |
| Gross weight | 0.75 kg |
| Shape of cut-out | round |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1006148 | Numinos® L Reducing ring , round 240/150mm white |
| 1006149 | Numinos® L Reducing ring , square 240/150mm black |
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1006150 | Numinos® L Reducing ring , square 240/150mm white |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1006147 | Numinos® L Reducing ring , round 240/150mm black |
| 1004070 | LED driver , 40W 700mA DALI |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1004065 | LED driver , 30W 700mA |

| | |
|-----------------------|---------|
| Installation depth | 11.5 cm |
| Installation diameter | 14.5 cm |
| BIG WHITE Page | 89 |