



## NUMINOS® GIMBLE XL

white / black recessed ceiling light, 4000K 20°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1006074                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 1000/1050 mA            |
| Safety class                      | III                     |
| Wattage                           | 37.4 W                  |
| Lumen                             | 3600 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 20 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 13.5 cm                 |
| Diameter                          | 19 cm                   |
| Net weight                        | 0.85 kg                 |
| Gross weight                      | 1 kg                    |
| Shape of cut-out                  | round                   |

## Light Source

|        |   |
|--------|---|
| 791850 |  |
|--------|---|

## Accessories

|         |   |
|---------|---|
| 1006152 | Numinos® XL Reducing ring , round 240/180mm white   |
| 1006151 | Numinos® XL Reducing ring , round 240/180mm black   |
| 1004800 | NUMINOS® XL , diffuser Frosted  |
| 1004071 | LED driver 4.2-50W 1050mA DALI  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                     |
| 1006154 | Numinos® XL Reducing ring , square 240/180mm white  |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                 |
| 1004798 | NUMINOS® XL , diffuser Ellipse  |
| 1006153 | Numinos® XL Reducing ring , square 240/180mm black  |
| 1004059 | LED driverm 40W multi mA  |
| 1006461 | LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004066 | LED driver , 28-40W 1000mA PHASE  |
| 1004801 | NUMINOS® XL , diffuser Wabe   |
| 1004799 | NUMINOS® XL , diffuser Prisma   |

|                       |         |
|-----------------------|---------|
| Installation depth    | 13.5 cm |
| Installation diameter | 17.5 cm |
| BIG WHITE Page        | 89      |