




## NUMINOS® SPOT XL PHASE

white / black ceiling mounted light, 36W 2700K 24°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® SPOT XL PHASE indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3290 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS® from SLV?



### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1006086                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Surface                 |
| Assembly details                  | Ceiling                 |
| Dimmable                          | Yes                     |
| Dimming technology                | trailing edge           |
| Primary nominal voltage           | 220-240V ~50/60Hz       |
| Secondary power / voltage         | 900 mA                  |
| Safety class                      | I                       |
| Wattage                           | 36 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 35 °C                   |
| Level of inrush current           | 4.64 A                  |
| Duration of inrush current        | 224 µs                  |
| Stroboscopic effect (SVM)         | 0.02                    |
| Lumen                             | 3290 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 24 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |

Light Source

|        |   |
|--------|---|
| 791857 |  |
|--------|---|

|                |         |
|----------------|---------|
| LXXBXX data    | L80B50  |
| Service life   | 50000 h |
| Risk Group     | 1       |
| Length         | 25.8 cm |
| Height         | 20 cm   |
| Diameter       | 12 cm   |
| Net weight     | 1.7 kg  |
| Gross weight   | 2.15 kg |
| BIG WHITE Page | 101     |