



DASAR FLAT 120 EL


stainless steel in-ground light, 7W 3000K

The DASAR FLAT 120 EL high-voltage recessed ground light can be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. Added to this is the high-quality housing made of 304 stainless steel. See the outdoor lights in action and let yourself be impressed by a stunning lighting experience.

TECHNICAL DATA

Item no.	1006106
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	0.5 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,5
Number of luminaires at LS B16A	112
Number of luminaires at LS C16A	200
Level of inrush current	10 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.4
Lumen	490 lm
Colour temperature	3000 Kelvin
Color	stainless steel

Light Source

916531		CRI	80
		LXXBXX data	L70B50
		Service life	30000 h
		Risk Group	1
		Depth	8 cm
		Diameter	12 cm
		Net weight	0.703 kg
		Gross weight	0.789 kg
		Shape of cut-out	round
		Installation depth	8 cm
		Installation diameter	10.6 cm
		BIG WHITE Page	839