



## NUMINOS® ZOOM M PHASE

white 3-phase spot, 20W 2700K 15-60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® ZOOM M PHASE 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

### TECHNICAL DATA

Item no.	1006109
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.03
Lumen	680-1650 lm
Colour temperature	2700 Kelvin
Beam angle	15 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L70B50
Service life	40000 h
Risk Group	1
Length	19 cm

Light Source

791800	
--------	---

Height	16.5 cm
Diameter	8.5 cm
Net weight	0.989 kg
Gross weight	1.294 kg
BIG WHITE Page	115