



NUMINOS® ZOOM M PHASE

white 3-phase spot, 20W 3000K 15-60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® ZOOM M PHASE 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1006111
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.03
Lumen	750-1800 lm
Colour temperature	3000 Kelvin
Beam angle	15 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L70B50
Service life	40000 h
Risk Group	1

Light Source

791822	
--------	---

Length	19 cm
Height	16.5 cm
Diameter	8.5 cm
Net weight	0.989 kg
Gross weight	1.311 kg
BIG WHITE Page	115