



OCULUS WL PHASE

Wall-mounted light white 8.5W 570lm 2000-3000K
CRI90 100° Dimmable

The OCULUS WL PHASE wall light emits a sharply delineated beam of light thanks to its special lens technology. This cylindrical aluminium and glass light also creates particularly welcoming illumination thanks to its high CRI of over 90 and the dim-to-warm function (2000-3000K). Ideal for GP practices, law offices, cafés, hotels, restaurants and the private sector. Establishing a simple, direct connection to a 220 volt mains supply is incredibly straightforward.

TECHNICAL DATA

Item no.	1006308
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Dim-to-Warm, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	8.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	2 A
Duration of inrush current	50 µs
Stroboscopic effect (SVM)	0.03
Lumen	57-570 lm
Colour temperature	2000-3000 Kelvin
Beam angle	100 °
Color	white
CRI	90
LXXBXX data	L70B50

Light Source

916398	
--------	---

Service life	25000 h
Risk Group	1
Height	8.75 cm
Depth	12.4 cm
Diameter	9 cm
Net weight	0.63 kg
Gross weight	0.674 kg
BIG WHITE Page	355