




M-POL M Polehead

Lamp head, anthracite, 11W, 470/510lm, 2700/3000K, CRI90

The different lamp heads in the DALI-dimmable SLV outdoor family offer a wide variety of options. With a CRI of over 90, 470 / 510 lumen, and an LED lifespan of 50,000 hours, the cylindrical M-POL S Polehead can satisfy even the most challenging requirements. Use the appropriate lamp head to implement specific outdoor projects.



TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1006383 |
| IP Code | IP 65 |
| Impact resistance class | IK 10 |
| Assembly details | Ground with Acc. |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Wattage | 11 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Operating efficiency (LOR) | 0,522 |
| Number of luminaires at LS B16A | 17 |
| Number of luminaires at LS C16A | 34 |
| Level of inrush current | 4.7 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 470/510 lm |
| Colour temperature | 2700/3000 Kelvin |
| Color | anthracite |
| CRI | 90 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |

Light Source

| | |
|---------|---|
| 1370513 |  |
|---------|---|

Accessories

| | |
|---------|---|
| 1006381 | M-POL 90 Pole , Bollard, anthracite, 83.4cm |
| 228726 | T-CONNECTION BOX , black, IP68 |
| 228730 | CONNECTION BOX , 3-pin, IP68 |
| 1006379 | M-POL 30 Pole , Bollard, anthracite, 23.4cm |
| 1006380 | M-POL 60 Pole , Bollard, anthracite, 53.4cm |
| 1006382 | M-POL ground anchor , stainless steel |

| | |
|----------------|----------|
| Height | 15.9 cm |
| Diameter | 12.09 cm |
| Net weight | 0.992 kg |
| Gross weight | 1.061 kg |
| BIG WHITE Page | 616 |