




M-POL S Polehead

Shader lamp head, anthracite, 11W, 285/310lm, 2700/3000K, CRI90

Suitable for universal use, featuring a sophisticated design and high output: the lamp heads and diffusers in the first DALI-dimmable SLV outdoor family are ideal for a variety of applications. The cylindrical M-POL S Polehead has a CRI of over 90, 285 / 310 lumen, and an LED lifespan of 50,000 hours, which can satisfy the most challenging lighting design requirements. Use the appropriate lamp head to implement specific outdoor projects.



TECHNICAL DATA

Item no.	1006387
IP Code	IP 65
Impact resistance class	IK 10
Assembly details	Ground with Acc.
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,317
Number of luminaires at LS B16A	17
Number of luminaires at LS C16A	34
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	285/310 lm
Colour temperature	2700/3000 Kelvin
Color	anthracite
CRI	90
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1

Light Source

1370513	
---------	---

Accessories

1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
228726	T-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006382	M-POL ground anchor , stainless steel

Height	15.9 cm
Diameter	12.09 cm
Net weight	1.052 kg
Gross weight	1.126 kg
BIG WHITE Page	617