




M-POL M Polehead

Lamp head, anthracite, 19W, 1150/1230lm, 2700/3000-K, CRI90, DALI

Suitable for universal use, featuring a sophisticated design and high output: the lamp heads and diffusers in the first DALI-dimmable SLV outdoor family are ideal for a variety of applications. With a CRI of over 90, 1150 / 1230 lumen, and an LED lifespan of 50,000 hours, the cylindrical M-POL M Polehead can satisfy even the most challenging requirements. Enjoy the flexibility to implement a diverse range of lighting projects.



TECHNICAL DATA

Item no.	1006390
IP Code	IP65
Impact resistance class	IK 10
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-24050/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0.561
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	16
Level of inrush current	10 A
Duration of inrush current	30 µs
Color	matt anthracite
Risk Group	1
Height	26.4 cm
Diameter	12.26 cm
Net weight	1.434 kg
Gross weight	1.772 kg

Accessories

1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
1006453	Y-CONNECTION BOX , 5-pin, IP68, black, DALI
1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006382	M-POL ground anchor , stainless steel
228725	CONNECTION BOX , 5-pin, IP68