




M-POL M Polehead

Shader lamp head, anthracite, 19W, 820/870lm, 2700/3000K, CRI90, DALI

Suitable for universal use, featuring a sophisticated design and high output: the lamp heads and diffusers in the first DALI-dimmable SLV outdoor family are ideal for a variety of applications. The cylindrical M-POL M Polehead has a CRI of over 90, 820 / 870 lumen, and an LED lifespan of 50,000 hours, which can satisfy the most challenging lighting design requirements. Choose a specific lamp head as preferred for your lighting projects.



TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1006394 |
| IP Code | IP 65 |
| Impact resistance class | IK 10 |
| Assembly details | Ground with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Wattage | 19 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Operating efficiency (LOR) | 0,397 |
| Rated standby power | 0.5 W |
| Number of luminaires at LS B16A | 8 |
| Number of luminaires at LS C16A | 16 |
| Level of inrush current | 10 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 820/870 lm |
| Colour temperature | 2700/3000 Kelvin |
| Color | anthracite |
| CRI | 90 |

Light Source

| | |
|---------|---|
| 1370514 |  |
|---------|---|

Accessories

| | |
|---------|--|
| 1006381 | M-POL 90 Pole , Bollard , anthracite, 83.4cm |
| 1006453 | Connection box , 5-pin, IP68, black, DALI |
| 1006379 | M-POL 30 Pole , Bollard, anthracite, 23.4cm |
| 1006380 | M-POL 60 Pole , Bollard, anthracite, 53.4cm |
| 1006382 | M-POL ground anchor , stainless steel |
| 228725 | CONNECTION BOX , 5-pin, IP68 |

| | |
|----------------|----------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 26.4 cm |
| Diameter | 12.26 cm |
| Net weight | 1.498 kg |
| Gross weight | 1.603 kg |
| BIG WHITE Page | 620 |