




## IN-LINE 22 48V TRACK

opal, DALI, spot, white 7.3W, 540lm, 2700K, CRI90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 35° beam angle in various lumen and natural colour reproduction (CRI>90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



## TECHNICAL DATA

Item no.	1006616
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	350 mA
Safety class	III
Wattage	7.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Stroboscopic effect (SVM)	0.4
Lumen	540 lm
Colour temperature	2700 Kelvin
Beam angle	95 °
Color	white
CRI	90
UGR ≤	28

Light Source



LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	22 cm
Width	2.2 cm
Height	5.5 cm
Net weight	0.167 kg
Gross weight	0.179 kg
BIG WHITE Page	473