


## NUMINOS® XS 48V TRACK

DALI, pendant light, white / black, 8.7W, 640lm, 2700K, CRI90, 55°

High-quality minimalism across the board: the compact NUMINOS® pendant lights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The pendant lights are quick and easy to install thanks to the track adapter.



### TECHNICAL DATA

|                                   |                      |
|-----------------------------------|----------------------|
| Item no.                          | 1006774              |
| Number of different light outlets | 1                    |
| IP Code                           | IP 20                |
| Impact resistance class           | IK 02                |
| Impact resistance                 | 0.2 Joule            |
| Assembly details                  | Track, Track Ceiling |
| Dimmable                          | Yes                  |
| Dimming technology                | DALI 2               |
| Primary nominal voltage           | 48V                  |
| Secondary power / voltage         | 200 mA               |
| Safety class                      | III                  |
| Wattage                           | 8.7 W                |
| Minimum ambient temperature       | -20 °C               |
| Maximum ambient temperature       | 35 °C                |
| Network rated standby power       | 0.5 W                |
| Lumen                             | 640 lm               |
| Colour temperature                | 2700 Kelvin          |
| Beam angle                        | 55 °                 |
| Color                             | white                |
| CRI                               | 90                   |
| UGR ≤                             | 25                   |
| LXXBXX data                       | L80B50               |

Light Source

|        |   |
|--------|---|
| 798300 |  |
|--------|---|

Accessories

|         |                                    |
|---------|------------------------------------|
| 1005614 | NUMINOS® XS , frosted diffuser     |
| 1005612 | NUMINOS® XS , diffuser             |
| 1005615 | NUMINOS® XS , black diffuser       |
| 1005613 | NUMINOS® XS , transparent diffuser |

|                |          |
|----------------|----------|
| Service life   | 50000 h  |
| Risk Group     | 1        |
| Height         | 8 cm     |
| Diameter       | 5 cm     |
| Pendant length | 150 cm   |
| Net weight     | 0.211 kg |
| Gross weight   | 0.226 kg |
| BIG WHITE Page | 471      |