## **Specialist • Lighting • Vendor**






## NUMINOS® XS 48V TRACK

DALI, pendant light, white / white, 8.7W, 670lm, 2700K, CRI90,  $55^{\circ}$ 

High-quality minimalism across the board: the compact NUMINOS® pendant lights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The pendant lights are quick and easy to install thanks to the track adapter.



#### **TECHNICAL DATA**

Item no.	1006775
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	200 mA
Safety class	III
Wattage	8.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Lumen	670 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR≤	25
LXXBXX data	L80B50
	<u> </u>

# Specialist • Lighting • Vendor



### **Light Source**

798300	Å F	
Accessories		
1005614	NUMINOS® XS , frosted diffuser	
1005612	NUMINOS® XS , diffuser	
1005615	NUMINOS® XS , black diffuser	
1005613	NUMINOS® XS , transparent diffuser	

Service life	50000 h
Risk Group	1
Height	8 cm
Diameter	5 cm
Pendant length	150 cm
Net weight	0.211 kg
Gross weight	0.226 kg
BIG WHITE Page	471