




NUMINOS® PROJECTOR XS

recessed ceiling light, 3000 K, 40°, cylindrical, black / chrome

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



TECHNICAL DATA

Item no.	1006890
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	8 cm
Diameter	4.9 cm
Net weight	0.24 kg

Light Source

798303	
--------	---

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Gross weight	0.257 kg
Shape of cut-out	round
Installation depth	10 cm
Installation diameter	6.8 cm
BIG WHITE Page	92