




## NUMINOS® PROJECTOR S

recessed ceiling light, 2700 K, 55°, cylindrical, white / chrome

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1006938                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 250 mA                  |
| Safety class                      | III                     |
| Wattage                           | 8.6 W                   |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 690 lm                  |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Length                            | 12.5 cm                 |
| Diameter                          | 6 cm                    |
| Net weight                        | 0.55 kg                 |

## Light Source

|        |   |
|--------|---|
| 791819 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe   |
| 1004067 | LED driver , 15W 250mA DALI  |
| 1004788 | NUMINOS® S , diffuser Frosted  |
| 1004787 | NUMINOS® S , diffuser Prisma   |
| 1004786 | NUMINOS® S , diffuser Ellipse  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1004058 | LED driver , 6.5-10W 250mA   |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1004055 | LED driver , 6.5-10W 250mA PHASE   |

|                       |          |
|-----------------------|----------|
| Gross weight          | 0.589 kg |
| Shape of cut-out      | round    |
| Installation depth    | 15 cm    |
| Installation diameter | 8.8 cm   |
| BIG WHITE Page        | 92       |